

Butylseal

Flexible Butyl Rubber Tape

Characteristics:	A butyl rubber tape with excellent elongation and a degree of memory Clean and easily placed in position Does not shrink Non soluble Permanently flexible Can be painted and plastered over For use on timber, plywood, fibre cement sheet, concrete, masonry block, gib and most metals
Preparation:	All surfaces must be free of oil, dust, wax, curing compounds, release agents, paint etc. and any protrusions They should be dry and free from excessive movement. Ensure all concrete surfaces have had sufficient cure time, and that all other surfaces are fixed in accordance with manufactures specifications and relevant standards. Metal surfaces must be rust free Prime surface with appropriate primer
Application:	After correct preparation place butyl tape ensuring any joins are overlapped minimum 50mm Apply pressure to tape to ensure it is well bonded to substrate Apply pressure with a roller to joints to mould them together
Clean up:	Scrape excess of substrate and place in container for correct disposal Clean with solvent using protective eyeware and gloves
Packaging/ Shelf Life:	Store in cool dry conditions on a pallet on on shelves in racking Store in a dry area in a temperature < 40 degrees celcius Available in 15 metre roll lengths in a width of 80mm and 150mm

Technical Data

Properties	Results
Appearance	Rubber mastic tape
Solids	100%
Physical Attributes	Deforms under compression and adheres to surface
Colour	Grey with white woven surface
Application Temperature Range	0 – 40 degrees celcius
Service Temperature Range	Minus 20 – 80 degrees celcius
% elongation at break	> 400%

The information supplied is to the best of our knowledge true and accurate. The actual application of the product is beyond the manufacturer's control. Any failure or damage caused by the incorrect usage of the product is not the responsibility of the manufacturer. The manufacturer insist that all workmanship must be carried out in accordance with acceptable trade practices It is also the responsibility of the end user to ensure that the literature in their possession is the latest issue.

Flexco (NZ) Ltd

67 Dalgety Drive, Manukau City, P: 0064 9 2686970, F: 0064 9 2686971, E: info@flexco-nz.co.nz
P O Box 98866 South Auckland Mail Centre, Manukau City, New Zealand



FLEXCO (N.Z.) LTD
SOLVING TOMORROWS BUILDING PROBLEMS - TODAY